

Torque Control > Bolt Load Control

Smart Bolting Technology Product Portfolio

Passion for Innovation Your Problem ~Our Inspiration

www.zipptork.com



CONCENT

- **ZIPPTORK** Bolting 4.0 Smart Bolting Solution
- ZIPPTORK Bolting Solutions Q & A
- Bolting Technology $\, \sim \,$ Common Issues in the Field
- Patents & ISO Certification
- Patents Granted for Bolting Technology
- Relevant Patents
- Bolting Technology Products Portfolio \sim

Torque Control

Bolt Load Control

- Torque Control Products Application Examples $\, \sim \,$ Before Bolting
 - During the Bolting Process
 - After Bolted
- Bolt Load Control Products Application Examples \sim Bolt Load Control During the Bolting Process Bolted Joint Monitoring
- Smart Bolting Control Products Application Examples $\,\sim\,$

Advanced Application Alternatives

How to select the proper Air Impact Wrench & Torque Transducer? Wheel Stud/Nut Bolting & Residual Torque Verification

Overview



ZIPPTORK has been working for decades on the development of various assembly technologies, such as the bolting of thread fasteners, the riveting or squeezing of solid or hollow rivets, the blind riveting of blind rivets or rivet nuts and HUCK type bolts, etc., with an emphasis on the intelligence of the related products.

The bolting control technology is an important development target for **ZIPPTORK**, mainly for torque control of thread fasteners, bolt load (clamping force) control and monitoring of bolted joint status. The portfolio brings together key equipment such as torque testers for the calibration, verification and simulation of tool torque capability before assembly, monitoring or controlling the tightening torque and bolt load (clamping force) during assembly, and residual torque detection after bolted, and continuous monitoring of the bolted joint status, either immediately or periodically, to ensure the highest reliability of the assembled equipment, all under one system with a complete patented layout.

With the advent of the smart factory, **ZIPPTORK** is an essential source of technological and engineering information to help you make Industry 4.0 a reality.

ZIPPTORK Bolting 4.0 - Smart Bolting Solution



Quality, efficiency and flexibility are three drivers of Industry 4.0. Digitalization allows industries to introduce effective processes to mass produce higher-quality products at lower costs. When talking about technologies, the cornerstones that are shaping Industry 4.0 for businesses are cloud computing; the Internet of Things; big data and analytics; additive manufacturing(3D Printing); and autonomous robotics. No wonder most industries are willing to move toward the industry of tomorrow. However, the budget for relevant investments becomes the most significant obstacle. Narrow the problem down to the bolting works popular in most industries. How to do the job faster, safer and more reliably while requiring the production record to be traceable for reliability and assurance of quality.

ZIPPTORK Bolting 4.0 provides innovative, effective, yet economical solutions for various industries in their daily bolting works, such as torque tool calibration, torque simulation before work, bolting control during the process and residual torque verification after bolt, and even the highest requirement to control every bolted joint with the same bolt load. At the same time, keep monitoring the bolted joint status remotely, periodically or continuously. It meets the application requirement of IoT.

You are welcome to visit and browse the website – <u>www.zipptork.com</u> for more information and videos.

ZIPPTORK Bolting Solutions Q & A



Bolting Torque / Bolt Load Control, Bolting Sequence Control, Bolted Joint Status Monitoring, Job Traceability & Data Collection/Logging

1. How to control the bolting torque of air or DC-driven impact wrench or pulse wrench? Air torque tools with TCA/TCB Controller or DC tool with built-in ECB Control board attached with TTE Torque Transducer under Transducer Mode ~ Torque controllability ±10% ~ ±15% accuracy for impact wrench, $\pm 5\% \sim \pm 10\%$ for oil pulse wrench Air torque tools with TCA/TCB Controller or DC tool with built-in ECB Control board only under Pressure or Voltage Mode ~ Torque controllability ±15% ~ ±20% accuracy for impact wrench, $\pm 10\% \sim \pm 15\%$ for oil pulse wrench 2. How to monitor the bolting torque of pulse wrench and clutch type tool? Auto shut off type oil pulse wrench or Clutch type wrench ~ Use TTE Transducer + DR-RF Dongle + Tablet for torque monitoring and data logging. Accuracy depends on tool quality. Non-shut-off type oil pulse wrench ~ Use method and apparatus of 1 mentioned above. 3. How to collect bolting data of a click-type wrench? Use Click type wrench + TTA/STA wireless Torque Transducer + DR-RF Dongle + Tablet to make audible "CLICKs" visible and data collectable. 4. How to measure the residual torque of a bolted joint with 1st movement method? Use any manual torque wrench + TTA/STA wireless Torque Transducer + DR- RF Dongle + Tablet to obtain the residual torque just at the 1st movement of the bolted joint while keep tightening. 5. How to measure the residual torque of an extremely high torque (over 500NM) bolted joint? Use any manual torque wrench + TTA/STA wireless Torque Transducer + TM(Torque Multiplier ~ up to 3 stacks of TM) + DR-RF Dongle + Tablet to obtain the residual torque just at the 1st movement of the bolted joint. 6. How to do torgue simulation of power-driven torgue tools before bolting? Use the tool with or without the TTE Torque Transducer attached \rightarrow TTT/LTT Torque Tension Tester+ DR-RF Dongle+ Tablet to measure the device's working torque under specific air pressure or voltage to tighten the particular fastener and acquire the working torque with correspondent bolting seconds. Please refer to the *appendix* for the solutions to the following questions! • How to do torgue control for car wheel bolting precisely and efficiently? Is there any practical alternative for ultrasonic bolting technology? How to monitor the bolted joint condition continuously or periodically? How to do high torque bolting? How to do bolting sequence control? • What is the most advanced transducerized power-driven torgue multiplier? • What is the ultimate solution of bolting works?

Bolting Technology



Common Issues in the Field

- How to select a proper torque tool? Tool Cost vs Control Accuracy
- How to manage bolting work before, during & after?
- How to do daily or periodic calibration with a record for traceability ?
- How to control the bolting torque of discontinuous drive torque tools such as an impact or pulse wrench?
- How to monitor the bolting torque of a clutch-type screwdriver and obtain relevant bolting data?
- How to monitor the bolting torque of a power torque tool with an auto shutoff mechanism and obtain relevant data?
- How to collect the bolted data once a click wrench checks it?
- How to digitalize an interchangeable head torque wrench and make it accessible with various types of heads from other brands?
- How can digital torque wrenches or transducers simultaneously measure the bolt load?
- How to do high torque bolting by several stages while bolting sequentially?
- How to verify the high residual torque over 500NM effectively & correctly?
- How to make an air motor with servo control?
- How to tighten wheel lug nuts properly with accurate torque control and bolting sequence while recording relevant data?
- How to measure & control the bolt load during the bolting process? Bolt Load Transducer is the answer
- How to control the bolt load of a bolted joint? A sensing Washer or Sensing Bolt will be an effective and economical alternative to ultrasonic bolting technology.
- How to monitor the tightened status of a bolted joint remotely? A sensing Washer or Sensing Bolt is the best choice.

Patents & ISO Certification





Patents Granted for Bolting Technology



ltem ²	Title↩	Country	Reference	Expiry-Date
1∉⊐	A-method-of-programmable-toque-controlling- for-sensing-bolt	USA∉⊐	US-2015/0041162-A143	Feb.12,-203543
2∉⊐	Anti-Vibration-Torque-Sensing-and-Control- Device-for-Tools	USA∉⊐	US-7,779,704-B143	Aug.·24,2030
3⊄⊐	Apparatus Capable of Controlling, Tracking and Measuring Tightening Torque and Locking Force, and Method for Controlling, Tracking, Measuring and Calibrating Thereof ¹²	USA∉∃	US-9,026,379-B2∉ ³	May-5,-2035
4∉⊐	Apparatus and Control System of Programmable Air Servo Motor	USA∉⊐	US·10,422,356·B2↩ [□]	Feb06,-2038∉3
5∉⊐	Torque Control System and Torque Control Method for Power Impact Torque Tool	USA∉⊐	US·10,940,577·B2↩ [□]	Sept10,-2038⇔
6∉⊐	Method of Torque Control and Apparatus Thereof	USA∉⊐	US·10,564,657·B2↩ [□]	Feb.·18,·2040€
7∉⊐	WIRELESS TORQUE TRANSDUCER 4	USA⇔⊐	US·D887,881·S↩ [□]	Jun.23, •2035∉⊐
8≓⊐	Monitoring-System and Method for a Bolting Operation	USA∉⊐	US·10,055,623·B2↩ [□]	Aug.·21,2038టె
تبو	扭力制御方法及方法的制御装置	Japan	特許第 6420848 號₽	Oct19,-20394
<mark>10</mark> ∉⊐	扭力感知及傳導装置	Japan≓	特許第 6871351 號ല	April-19,-2041
<mark>11</mark> ↩ [□]	Drebmomentverstarker	Germany	Pat.·Nr.·10·2017·127·762∉ ³	15.11.2038년
12∉⊐	Digitales Anzeigegerat für ein werkzeug zum Anziehen von Befestigungsmitteln	Germany	Pat. Nr. 20.2010.005.469.94	20.05.2030년
تب13	Drehmomenststeteuersystem und- Drehmomentsteuerve fahren: fur Elektro, Schlagwerkzeug: mit Einstellbarem, drehmoment: 電影推進中	Germany	PatNr10-2017-119-623∉	28.08.2037
14∉⊐	Druckluftsteuerungsmoduleinhelt, fur tragbare, druckluftbetatigte.Werkzeuge	Germany	PatNr20-2007-007-127.243	04.11.2030
1543	Uberwachungssystem; und- Uberwachungsverfahren; zur- Schraubenverbindung; ²¹	Germany∉	PatNr10-2017-104-22443	10.12.204043
16¢ ^{_3}	Darstelllung:1-von-7-(-Wireless-Torque- Transducer-(無線扭力傳感器外型專利)- ₽	Germany∉	Designs-Nr. 402018100941-0001, 0002, 00034	09.18.2043년
17∉⊐	螺栓 <u>夹紧力或應</u> 垫圈≓	Taiwan∉	<u>新型算_</u> M598351 號≓	2030.04.12
18∈⊐	動力鎖緊工具之扭矩控制装置及其控制程序。	Taiwan	發明第-1-396609 號≓	2030.07.13
1 9 ∉⊐	扭力感测與傳輸裝置₽	Taiwan	發明第 1-703315 號≓	2039.01.09
20년	感應螺栓的電源與訊號傳輸裝置及感應螺栓 裝置₽	Taiwan	發明第-1-664356 號₽	2037.03.23
21∉⊐	螺栓分次锁固的扭力控制方法及扭力控制装 置	Taiwan⇔	發明第-1-670149 號≓	2038.06.06
22∉⊐	可程式氣動伺服馬達	Taiwan	發明第一584919 號≓	2036.05.18
23∉⊐	<u>螺栓鎖固作業</u> 的監控系統及其方法 ⁽²⁾	Taiwan	發明第-1-569923 號₽	2036.07.04

24∉⊐	具扭力、角度感测及訊號傳輸功能 <u>的套簡</u> 。	Taiwan	發明第-1-631323 號↩	2037.10.29				
25∉⊐	電動衝擊式扭力工具的扭力控制系統及 <u>其扭</u> 控制方法₽	Taiwan₽	發明第·Ⅰ-619582 號↩	2037.06.08				
26టె	氟動衝擊式扭力工具的扭力控制方法及其扭 力控制系统↔	Taiwan≓	Taiwan- 發明第 1592778 號→ 2036.02.0					
27↩□	扭矩颞示系统及其方法↩	Taiwan∉	發明第-1-435795 號↩	2031.10.02				
28∉⊐	具有抗振作用之工具扭力或應與控制装置 ¹¹ Taiwan ¹¹ 發明第 1342821 號 ¹¹ 2029.01.20 ¹¹							
29¢ ²	扭力控制方法及其扭力控制装置 [↓] Taiwan [↓] 發明第-1509379 號 [↓] 2034.07.30 [↓]							
30∉⊐	<u>衛擊式氣動扭力板手之</u> 扭矩控制裝置 [↓] Taiwan [↓] 發明第一1432293 號 [↓] 2032.01.03↓							
31↩□	可控制與追蹤 <u>量測錄緊</u> 扭矩 <u>及錄緊力</u> 的裝置 及其控制方法、追蹤量測方法與校驗的方法。	<u>办</u> 的菜置 <u>教</u> 的方法 [↓] Taiwan↓ 發明第-1454346 號↓ .						
32↩コ	動力鎖緊工具之扭矩控制装置及其控制程序₽	Taiwan↩	發明第一Ⅰ-396609 號₽	2030.07.13				
33∉⊐	無線扭力傳感器之部分₽	Taiwan↩	設計第 D197509 號≓	2030.07.13				
34∉⊐	間接耦合之扭矩控制方法及其機構。	Taiwan	發明第一Ⅰ-498196 號↩	2032.10.04				
35∉⊐	間接藕合的扭矩控制方法及其機構□	China⇔	ZL·2012·1·0414390.·8∉∃	2035.09.16				
36∉⊐	具有抗振作用的工具扭力感應與控制裝置↩	China↩コ	ZL·2010·1·0101192.·7	2032.02.01↩□				
37↩⊐	扭矩顯示系統及其方法↓□	China	ZL·2011·1·0138293.·6	2033.12.25				
38⋳⊐	感應螺栓的電源與訊號傳輸裝置及感應螺栓 裝置	China⇔	ZL-2017-1-0181401543	2039.11.22↩コ				
39⊬⊐	電動衝擊式扭力工具的扭力控制系統及 <u>其扭</u> 控制方法↔	China⇔	ZL·2017·1·0492652.·5↩3	2037.06.25				
40↩⊐	無線扭力傳感器 ^라 China ^라 ZL·2018·3·0512525.·2 ^라 2029.01.11 ^라							
41↩⊐	独力控制方法及其扭力控制装置 ^{↓1} China ^{↓1} ZL·20141·0371437.6 ^{↓1} 2037.06.06 ^{↓1}							
42↩□	可控制與追蹤測量鎖緊扭矩 <u>及鎮緊力</u> 的裝置 及相關方法 ⁽¹⁾	China	ZL-2012-1-0011877143	2034.02.26				
43∉⊐	可程式氣動伺服馬達的裝置與控制系統4	China↩コ	ZL·2016·1·0373780.·3∉∃	2036.05.29				
44↩	氯勤衝擊式扭力工具的扭力控制方法及其扭 力控制系统4	China↩コ	ZL-2016-1-00728639↩ [□]	2039.11.29				
45∉⊐	<u>爆栓镇固作業</u> 的監控方法+1	China↩コ	ZL-2016-1-0527106643	2040.01.31				
46↩□	螺栓分次缆固的扭力控制方法及扭力控制装 置43	China	ZL-2018-1-0577911943	2038-06-06				
申請中的專利~~								
● → 美國遷 <u>缺夾緊力</u> 傳感器+可擴充儲力板手扭力的裝置·								
●→日本還 <u>缺夾緊力</u> 傳感器+可擴充 <u>倍力板</u> 手扭力的裝置↔								
●→ 徳國逐 <u>級股登刀</u> 得風器+可撥死 <u>償力板</u> 手推力的衰量,↓ ●→ ム際運動北區力使素等外型重制,北區力使素等,可接方位力上系加力从世界/								
● > 古湾逐 <u>概代系ル</u> 得歐高外型导剂+ <u>展系ル得歐義</u> +可擴九 <u>微ル政</u> 元程力的裝置↓ ● → 土陸漫純水堅力債感至止水堅力債感至止可提在位力佔毛拉力的发展↓								
●→ 大陸逐 <u>缺夾发力</u> 傳感器+ <u>夾发力傳感器</u> +可擴充 <u>儲力板手</u> 扭力的裝置。→								



Bolting Control Products Portfolio

P.10~P.43

ZIPPTORK Smart Bolting Technology



As technology continues to transform the world of bolting threaded fasteners, more and more industries are exploring the benefits of intelligent bolting over manual or traditional torque tools. With promises of enhanced productivity, increased reliability, controllability and traceability, *ZIPPTORK* provides bolting technologies with extraordinary patented designs, control algorithms and devices not only make impact wrenches torque controllable but also make the bolted joint condition such as bolt load, ambient temperature and vibration detection possible for remote monitoring periodically or continuously.

ZIPPTORK Bolting Technologies includes two categories, i.e.

1. Torque Control System - consists of

- a. Torque Controller For controlling the torque of air or DC-powered impact and pulse wrenches.
- b. Anti-vibration Wireless Rotary Torque Transducer For monitoring static or dynamic bolting torque wirelessly.
- c. Wireless Swing Type Torque Transducer For monitoring bolting torque of interchangeable head torque wrench.
- d. Torque Tester For the test, calibrate torque tool output torque capability.
- e. Torque Tension Tester For measuring or simulating the bolt load induced with its equivalent residual torque while tightening specific thread fasteners to form a bolted joint under predetermined operating conditions.

2. Bolt Load Control System - consists of

- a. Anti-vibration Sensing Washer To control the bolt load induced on the bolted joint throughout the process and monitor the bolted joint status remotely, periodically or continuously.
- **b. Wireless Anti-vibration Bolt Load Transducer** Sensing and controlling the bolt load induced on the threaded fasteners throughout the bolting process.

It's an evolution of torque tool designed for measuring the bolt load instantly during the process.

Torque Control & Bolt Load Control System

IPPTORK Bolting Technology



SWC Sensing Bolt / SBC Sensing Washer Granted Patents Anti-vibration wireless Bolt Load Transducer Anti-vibration Sensing Washer Bolting Sequence Control Method



WTT Wireless Tension Transducer



Bolt Load Transducer

Can be fastened by any type of manual & air or DC driven impact or pulse wrench of ANY BRAND with ANY TORQUE MECHANISM



The ONLY Torque Controller capable to control Air or Cordless impact & pulse wrenches in the field



Cordless Wrench with built-In ECB Controller



Torque Control System



STA

TTAS/TTES/TTEH/TTEB Swing Type Torque Transducer Rotary Type Torque Transducer

> Applicable to any type of air & cordless impact or pulse wrench of ANY BRAND with ANY TORQUE MECHANISM

ZIPPTORK Bolting Control Series Products



							Type·No.↩	Description ←	Functions↩
		_ 1					TCA/TCB/TCC	Torque∙Controller⇔	For any type of air torque tools torque control regardless of type and brande
	1000 - 111 						ETCI / ETCP	Cordless∙ Controller	For-torque-control-of-any-type-of-DC-Cordless-torque-tools-with-built- in-Control-Board
	and a second sec	ZIPPSS 40Abum	18v				ттт/цтт∉	Torque∙Tension∙ Tester∉	For measuring or simulating the bolt-load-induced with its equivalent residual- torque while tightening specific thread fasteners to formed a bolted joint- under-predetermined operation condition. ⁽⁴⁾
TCA /	TCB / TCC Controller	ETCI / Built-In C	/ ETCP Controller Torg	TTT ue Tension Tes	ter To	LTT prove Tension Tester	TTS/TTL≓	Torque∙Tester	For-test, calibrate-torque-tool-output-torque-capability-TTS10 ~ 500NM, TTL-1,000 ~ 5,000NM ⁽⁻³
lorque							LTS/LTL=	Torque∙Tester	For test, calibrate-torque-tool-output-torque-capability \circ LTS1 \sim 50NM, \cdot LTL100 \sim 50,000NM $^{\oplus3}$
				The second		7119 1888	TTAS∉∃	Static·Transducer⇔	For manual-torque tool-calibration and residual-torque-verification with torque and angle ${}^{\triangleleft}$
						PECas - weather control of the Characteristic and a second second second the Characteristic and the Characteristic and the second se	TF↩┘	Test∙Fixture	$Used\text{-}with\text{-}TTAS\text{-}for\text{-}static\text{-}torque\text{-}calibration\text{-}or\text{-}measurement. {} { \in } { } { } { } { } { } { } { } {$
TTS				TTAS/TTFS		TTEP	TTES∉⊐	Dynamic∙ Transducer∉	Attached to tool anvil for dynamic torque control or torque monitoring during the bolting process. ←
Torque Tester	forque Tester	Torque Tester To	orque Tester Torq	ue Transducer	Torque	Transducer With bits	TTEH€	Dynamic∙ Transducer-with∙ Socket-in•One⇔	TTES-built-with-Socket-at-output-end-instead-of-the-square-anvil+3
							TTER€	Dynamic∙ Transducer-with∙ Reader∉	TTEH-with-built-In-Reader-for-reading-ID-of-Tagged-Bolt-or-Tag-Cell-on-the-bolt- end-and-transmitting-to-Torque-Controller-for-bolting-sequence-control
							BLT€	Bolt•Load• Transducer∉	For sensing and controlling the bolt load induced during bolting process with pre-calibrated parameter for each type of specific thread fastener ⊂
							WTT↩	Wireless∙ Tensioner∉	For sensing the tension <u>{-load</u> .} of the crane , hoist or winch and transmitting wirelessly with functions of overload alert and data collection or uploading ←
TTEH	ТТЕН		STA	BI	IT	WTE	SWB↩┘	Sensing•Washer- One•Piece•Type∉	Designed for fastener size over M20 或 3/4℃ for bolt load sensing and bolted joint remote monitoring
Torque Transducer With Socket	Torque Transo with Read	ducer Swing Type	e Torque Transducer	Bolt Load	Fransducer	Wireless Tensioner	SWC↩	Sensing∙Washer- split•Type⇔	Designed for small size under M20 或 3/4℃ for bolt load sensing and bolted joint remote monitoring
							ZG-SW↩	Gateway-SW∉	For-collecting-data-and-transmitting-to-peripheral-device-or-cloud-server-and- functions-for-monitoring-bolted-joint-status
					BP∉	Bolt Positioner	For-bolt-positioning-and-pair-with-Controller-during-the-bolting-sequence- control←		
							TB←	Tagged-Bolt↩	Bolt-with RFID Tag-embedded on bolt end for identification during bolting sequence control and read by Transducer with Reader €3
SWB	SWC	SBC	STR/STL	SG	TDR	SG	TC←⊐	Tag∙Cell€	To be adhered to bolt end for bolt identification during bolting sequence control and read by Transducer with Reader€
Sensing Washer	Sensing Washer	Sensing Bolt	Transmitter	Gateway	RF Dongle	SW/SB-Gateway	ZD€∃	Dongle⇔	For transferring sensed torque or bolt load or tension data to cellphone, tablet or laptop 디



Torque Control Products Portfolio

P.14~P.31

ZIPPTORK Bolting Technology



Torque Control Series

ZIPPTORK provides a full range of intelligent solutions for bolting works in various industries, including daily calibration of torque tools for bolting operations, torque simulation and adjustment of torque tools before bolting, monitoring or controlling tightening torque during the bolting process and residual torque verification after a run, etc.

Regardless of the brand and type of torque tools used in the production line, almost all torque monitoring, controlling and related data collection and uploading can be achieved.

Through this cost-effective solution, Industry 4.0 can be implemented to improve production with efficiency and industrial competitiveness.

You are welcome to visit and browse the website – www.zipptork.com for more information and videos.

Torque control for discontinuous drive torque tools ZIPPTORK Bolting Technology

To meet the industrial development trend of Industry 4.0, our company has launched a full range of patented products related to bolting technology, providing cost-effective solutions for the industry. Such as torque tool calibration, tool torque simulation & adjustment before work, bolting torque monitor or control during the bolting process, and residual torque verification after bolting; we can fully satisfy the application requirements of the Industrial Internet of Things(**IIOT**).

Wireless Rotary Torque Transducer / Swing Type Torque Transducer

- It is suitable for various types of torque tools output torque calibration or residual torque verification, as well as with various
 pneumatic or electric impact type, oil pulse type, clutch type torque tools with automatic shutoff mechanism for real-time
 torque monitoring and data collection of bolting torque.
- With a patented anti-vibration design, it is the only wireless torque transducer in the industry that can be used for high-vibration impact torque tools and torque control.
- Digitalization of "Interchangeable Head Torque Tools" for control & display bolting torque and angular movement in real-time and accessible with "HEADs" from any brand and joint mechanism.

Torque Controller

- Capable of controlling bolting torque of any discrete type air/DC cordless impact wrenches, oil pulse wrenches of any brand and any impact mechanism, and collecting data for uploading in real-time.
- Designed with patented control device and algorithm. It's the only air/DC driven continuous or discontinuous torque tool controller in the field, Three control modes are available for option, with the following control accuracy;

Pressure/Voltage Mode

Air/DC Impact Wrenches within $\pm 15\% \sim \pm 20\%$ & Air/DC Oil Pulse Wrenches within $\pm 10\% \sim \pm 15\%$

Transducer Mode

Air/DC Impact Wrenches within $\pm 10\% \sim \pm 15\%$ & Air/DC Oil Pulse Wrenches within $\pm 5\% \sim \pm 10\%$ Accumulated Mode

Air/DC Impact Wrenches within $\pm 10\% \sim \pm 15\%$ & Air/DC Oil Pulse Wrenches within $\pm 5\% \sim \pm 10\%$



Smart Series

Torque Controller / Wireless Torque Transducer / Torque Tension Tester / Dongle

Applicable to any Air Impact wrench/ Oil Pulse tool regardless of brand & torque mechanism



ZIPPTORK Bolting Control Series Products



Torque Controller





- 1. Applicable to any brand air-driven continuous or discontinuous torque tool with any mechanism.
- 2. Patented torque control device and control algorithm.
- 3. Patented programmable bolting sequence control.
- 4. Three control modes Pressure / Transducer / Accumulated
- 5. Batch count, barcode scanner, light Indicator, OK/NOK alert and record, and various job assemblies are available for ease of operation and user-friendliness.
- 6. Support POS for printing job result.

Torque Controller Application System Architecture Bolting Technology Torque Control > Bolt Load Control

PPTO





Torque Controller







- 1. Applicable to any brand air discontinuous drive torque tools with any mechanism.
- 2. The only torque controller for air impact/pulse/torque multiplier wrenches.
- 3. Patented control algorithm with excellent controllability.
- 4. Patented control method for bolting sequence control.
- 5. Three control modes Pressure / Transducer / Accumulated
- 6. Batch count, barcode scanner, light Indicator, OK/NOK alert and record and various job assemblies are available for ease of operation and user friendly.
- 6. Support POS for printing job results.

Torque Controller Application System Architecture







Torque Controller

Features



2.



- 1. Applicable to any brand air discontinuous drive torque tools with any mechanism.
 - The only torque controller for air impact/pulse/torque multiplier wrenches.
- 3. Patented control algorithm with excellent controllability.
- 4. Patented control method for bolting sequence control.
- 5. Three control modes Pressure / Transducer / Accumulated
- 6. Batch count, barcode scanner, light Indicator, OK/NOK alert and record and various assemblies are available for ease of operation and user friendly.
- 1. Support POS for printing job results.

Torque Controller Application System Architecture ZIPPTORK Bolting Technology





Cordless Wrench with built-in Torque Controller



- 1. Patented control board and control algorithm applicable to any continuous or discontinuous types of cordless torque tools.
- 2. Three control modes ~ Voltage / Transducer / Accumulated
- 3. Bluetooth communicate with a laptop or tablet for data access and up-loading.
- 4. Batch count, barcode scanner, light Indicator, OK/NOK alert and record various of job assembly are available the ease of operation and user friendly.
- 5. Support POS for printing job result.

Cordless Wrench Application System Architecture

PP

Bolting Technology Torque Control > Bolt Load Control





Wireless Rotary Torque Transducers



DR-RF DONGLE+ Laptop / Tablet



TTAS/TTES/TTEH/TTEB/TTER Wireless Rotary Torque Transducers

- 1. Patented anti-vibration design for durability.
- 2. The only wireless torque transducer applicable to air impact wrenches and Air/DC driven impulse wrenches.
- 3. Wireless features for the most excellent maneuverability, especially during bolting.
- 4. For measuring, monitoring and recording torque before, during or after assembly.
- 5. Designed for torque testing Provide solutions for most torque auditing applications in the manufacturing and quality department.
- 6. For testing the capability of your power torque tools, verifying the accuracy of your hand tools, monitoring the capability of your fastening process or auditing the quality of your assembled joints.
- 7. Data logging to peripheral devices or cloud servers for multiple transducers via Gateway.
- 8. Capacity range from 5NM ~ 3, 000NM.
- 9. Socket drive type-TTEH can be custom-made.
- 10. The only durable wireless transducer with a warranty of ONE year or 200 000 times dynamic bolting & 500 000 cycles of static bolting in the field.



Wireless Swing Type Torque Transducers



DR-RF DONGLE+ Laptop / Tablet



- 1. Patented design the only swing-type torque transducer to be mounted & detachable between the "Interchangeable Head Wrench" & "Head".
- 2. Wireless design for excellent maneuverability.
- 3. Digitalize conventional "Interchangeable Head Wrenches" for torque and angle control throughout the process & residual torque verification after bolting.
- 4. Head Adaptor design for easy replacing various types of HEADs, increasing the maneuverability and convenience of use.
- 5. Transmitting data wirelessly via RF2.4G to Gateway and a peripheral device or cloud server.
- 6. Available torque capacity range from 20NM to 1000NM.
- 7. One year or 500 000 cycles warranty.



Torque Tester



- 1. Ideal for torque calibration of manual, click, clutch type wrenches and torque multipliers
- 2. For measuring output torque of discontinuous type torque tools such as air or DC driven impact or impulse type wrenches.
- 3. Use torque sensor instead of hydraulic fluid to avoid oil leakage
- 4. Data logging to peripheral devices or cloud servers for multiple transducers via Gateway.
- 5. TTS series Torque Tester capacity available from 10NM up to 500NM
- 6. TTL series Torque Tester capacity available from 500NM up to 5, 000NM
- 7. Free software for self-calibration
- 8. To be equipped with Dongle & laptop or tablet for display and data collection.
- 9. One year or 500 000 cycles warranty.



Torque Tester

Features



LTS / LTL Torque Tester

- 1. Robust structure with leverage mechanism as calibration beam design.
- 2. Ideal for torque calibration of manual, click, clutch type wrenches and torque multipliers
- 3. For measuring output torque of discontinuous type torque tools such as air or DC driven impact or impulse type wrenches.
- 4. Use load sensor instead of weights on calibration beam (NORBAR) for compact design and easy operation.
- 5. Data logging to peripheral devices or cloud servers for multiple transducers.
- 6. LTS series Torque Tester capacity available from 1NM up to 50NM
- 7. LTL series Torque Tester capacity available from 100NM up to 50,000NM
- 8. To be equipped with Dongle & laptop or tablet for display and data collection.
- 9. One year or 500,000 cycles warranty.



TTA/TTE (Wireless Torque Transducer) + TF (Test Fixture)



- 1. Ideal for torque calibration of manual, click, clutch type wrenches and torque multipliers
 - . For measuring output torque of discontinuous type torque tools such as air or DC driven impact or impulse type wrenches.
 - . Portable for easy operation.
 - Data logging to peripheral devices or cloud servers for multiple transducers.
 - This series Torque Tester capacity is available from 10NM up to 3, 000NM
 - Free software for self-calibration
 - To be equipped with Dongle & laptop or tablet for display and data collection.
 - . One-year or 500,000 cycles warranty.



Torque Tension Tester

Features

- 1. Measure bolt load and residual torque equivalent induced after tightening by power-driven impact or pulse-type torque tools to fasten specific sizes of fasteners (bolt/ nut and washer) through the threaded mechanism.
- 2. Ideal for tool manufacturers to specify the dynamic tool specification accurately.
- 3. Can be used with hand torque wrenches, air impact/pulse wrenches, electric impact/pulse wrenches and hydraulic wrenches.
- 4. Good devices for simulating dynamic bolting torque of impact or pulse wrenches.
- 5. TTT series designed with one tester for replacing two sizes of sensors for fasteners in metric or imperial specifications.
- 6. 10 NM up to 5, 000NM test capacity ~ special requirement can be custom made.
- 7. Free software for self-calibration with different specifications of fasteners.
- 8. Connect Gateway to collect data and upload it to the cloud server.
- 9. Equipped with Dongle to display the torque and force curve on a tablet or laptop.
- 10. One year or 500 000 cycles warranty.

TTT

Torque Tension Tester

DR-RF DONGLE+ Laptop/Tablet

(h)



Torque Tension Tester



- 1. Measure bolt load and residual torque equivalent induced after tightening by power-driven impact or pulse-type torque tools to fasten specific sizes of fasteners (bolt/ nut and washer) through the threaded mechanism.
- 2. Ideal for tool manufacturers to specify the dynamic tool specification accurately.
- 3. Can be used with hand torque wrenches, air impact/pulse wrenches, electric impact/pulse wrenches and hydraulic wrenches.
- 4. Good devices for simulating dynamic bolting torque of impact or pulse wrenches.
- 5. LTT series designed with one tester for replacing four sizes of fasteners in metric and imperial specifications.
- 6. 10NM up to 5, 000NM test capacity special requirement can be custom made.
- 7. Free software for self-calibration with different specifications of fasteners.
- 8. Connect Gateway to collect data and upload it to the cloud server.
- 9. Equipped with Dongle to display the torque and force curve on a tablet or laptop.
- 10. One year or 500 000 cycles warranty.



Bolt Load Control Products Portfolio

P.33~P.43

ZIPPTORK Bolting Technology



Bolt Load Control Series

ZIPPTORK not only provides a full range of intelligent solutions for bolting operations in various industries but also provides control of bolt load (clamping force) during the bolting process for applications that require precise control of the clamping force of thread fasteners and monitoring the bolted joint status for abnormalities, such as high-pressure vessels, precision transmission or transportation facilities, or high-risk equipment for nuclear power and wind power. It also remotely monitors the bolted joint status after bolting and collecting and uploading relevant data.

It is the best alternative to the ultrasonic bolting technology commonly used in the industry, as it can be used with any brand and different structural designs of torque tools. Through this cost-effective solution, we can help the industry to realise the Industry 4.0 plan and further improve the productivity and competitiveness of the industry.

Bolt Load Control of Threaded Fasteners



To meet the industrial development trend of Industry 4.0, our company has introduced a full range of patented products related to bolt-tightening technology, which provides a cost-effective solution for the industry. Bolting of threaded fasteners is affected by many factors, such as the softness of the material of the fasteners (bolts, nuts and washers) and the surface roughness of the fasteners to be tightened, the influence of bruises or oil contamination on the threads during the process, and the difference in the structure and quality of the tools used, all of which make it difficult to control accurately and effectively. Furthermore, for the most crucial purpose of bolting works ~ the clamping force applied to the bolted joint, most of the industry can only control the clamping pressure of the bolt load by ultrasonic sensing & bolting technology. Some applications even require monitoring the bolted joint status after bolted and real-time notification when abnormal conditions occur. For this purpose, **ZIPPTORK** has developed a series of bolt load control technologies to provide the ultimate solution for threaded fastener tightening works, fully meeting the requirements of the Industrial Internet of Things(**IIOT**) applications.

Sensing Bolt & patented anti-vibration Sensing Washer for bolt load control & monitoring

It is ideal for all bolt-tightening operations requiring precise clamping force control and monitoring of the bolted joint status at any time. The patented anti-loosening design and ease of use make it more advantageous than the conventional ultrasonic sensing & bolting technology in mainstream applications as a great cost-effective alternative.

Patented Bolt Load Transducer

It can be used with any brand, type, or design of manual, pneumatic or electric torque tools to directly control and display the corresponding clamping force generated on the bolted joint by the applied torque at the time and can collect relevant data. It overturns the traditional method of controlling the bolting torque with torque tools. It directly measures the clamping force induced in the bolted joint instead, effectively improving the quality of bolting operations. A new era of "Bolt Load Wrench" is to come! For more product-related information and operation videos, please visit the following website – www.zipptork.com

The Ultimate Solution of Bolting Technology



Sensing Washer with functions of anti-loosening for controlling bolt load and monitoring the bolted joint status

1. What is different from past products or current market products?

Currently, the following methods are commonly used to test the clamping force in the market:

- Ultrasonic inspection method This inspection method is time-consuming, labor-intensive and expensive.
- Wired sensor bolt This test method is wired, challenging to achieve wirelessly, and expensive.
- Load cell This inspection method is wired, challenging to achieve wirelessly, and expensive.
- The clamping force control is only for the sensor to connect to the PLC or other display device by wired; the layout of the bolt load sensor of these methods is laborious and time-consuming, and the clamping force sensor does not have any anti-loosening design and does not have the bolting sequence control function.
- 2. Our company has been in the field of pneumatic tools for more than 40 years and has been dedicated to research and development of bolting technology for decades. However, in the area of bolting operation, torque control is not the most accurate technology, but bolt load (clamping force) control is the ultimate and most precise method; since the bolt load sensor is more expensive than the torque sensor, the market is still dominated by torque control. In recent years, customers' demand for bolting work and data recording has been increasing, and there is an urgent demand for clamping force control in the market. Therefore, our company has spared no effort to innovate and break through in research and development to make the best and ultimate clamping force control and monitoring for thread fasteners.

The Ultimate Solution of Bolting Technology



Sensing Washer with functions of anti-loosening for controlling bolt load and monitoring the bolted joint status

3. Due to the difficulty in mass production of the wireless bolt load sensor, the Sensing Bolt developed by our company at the beginning is hard to improve the yield rate and reduce the cost. With our efforts, we have finally developed a new generation of Sensing Washers to replace the **Sensing Bolts**, which have the following advantages:

- The **Sensing Washer** is suitable for both wireless communication and wired connection.
- The wireless Sensing Washer is ideal for small magnetic field interference fields such as the automotive industry, oil mining industry, etc.; the wired induction spacer is suitable for large magnetic field interference fields, including the construction and bridge industry, aerospace industry, etc.
- Low production cost and high yield rate
- Anti-loosening design (the sensing bolt itself does not have an anti-loosening plan) this anti-loosening design is patented.
- In practice, it is easy to carry, install, and operate.
- Higher accuracy and stability than sensing bolts, with dynamic bolt load control accuracy of ±10% and static bolt load control accuracy of ±5%.
- No need to use special or custom-made bolts. Use available bolts and sensing washers to achieve the following functions:

During the bolting process:

- The bolting sequence can be controlled with our innovative controller and tag.
- Bolt load control
- Torque equivalent for reference

After bolted, combined with Industry 4.0-IoT:

- Bolted joint (bolt load-clamping force) monitoring
- Torque equivalent display
- Clamping force, torque equivalent abnormal alarm
- Applicable tools: Any brand of manual, pneumatic and electric torque tools (static, impact, hydraulic pulse)
- Application: Construction, oil, mining, automotive, aerospace, etc., where clamping force monitoring is required.
- Applicable environment: High magnetic field interference environment, lightning strike environment...etc.
- The application can be used not only with our self-developed controller to achieve the clamping force and bolting sequence control but also as a stand-alone device. The detailed application structure is attached.

The Ultimate Solution of Bolting Technology



Bolt load Sensing Washer features with patented anti-vibration design for loose-proof and functions of remote monitoring the joint status instantly, periodically or continuously

1. What's the difference with compatible products in the field?

Current bolt load measuring methods, such as:

(1)Ultrasonic bolting technology—Time-consuming and expensive, no vibration loose-proof after bolting.
(2)Sensing Bolt—Hard to be built wirelessly and expensive, no vibration loose-proof after bolting.
(3)Load cells—No vibration loose-proof, only suitable for load testing, not ideal for industrial use.

2. Why use **ZIPPTORK** Sensing Washer?

- a. High sensitivity. As accurate as ultrasonic bolting technology.
- b. Patented anti-vibration design for perfect loose-proof and meet DIN65151 standard.
- c. Ideal for high-precision bolting work where clamp load control is critical and remote monitoring is required.
- d. Data collection for the highest traceability to ensure the most excellent safety.
- e. This is the ultimate solution for bolting works to reach the excellence of the bolted joint.

Bolt Load Control Series Products



Sensing Bolt / Sensing Washer / Wireless Bolt Load Transducer

Ideal for critical bolted joints where bolt load control is important & bolted joint status monitoring is required

Precision bolt load control / Patented anti-vibration design / ideal for transmission equipment Remote monitoring after bolted / The ultimate solution of bolting technology The most economic & effective alternative of ultrasonic bolting technology



Anti-vibration Sensing Washer



SW Sensing Washer





data link

- 1. Patented anti-vibration design to ensure the best stability of the bolted joint.
- 2. Bolt axial load control during bolting process by any torque tool.
- 3. Bolt joint status such as bolt load, temperature and vibration variation remote monitoring.
- 4. The best alternative for transmission equipment preventive maintenance work.
- 5. Applicable to any axial load joint status monitoring including HUCK lockbolt.
- 6. Remote monitoring bolted joint periodically or continuously and alert as soon as reach the preset threshold.
- 7. The most economic yet effective alternative of ultrasonic bolting technologies.
- 8. SWBN/SWBR should be custom-made. Please contact Sales personnel.

Anti-vibration Sensing Washer Application System Architecture ZIPPTORK



Sensing Bolt



SBC Sensing Bolt



data link

- 1. Bolt axial load control during bolting process by any torque tool.
- 2. Bolt joint status such as bolt load, temperature and vibration variation remote monitoring.
- 3. The best alternative for transmission equipment preventive maintenance work.
- 4. Remote monitoring bolted joint periodically or continuously and alert as soon as reach the preset threshold.
- 5. The most economic yet effective alternative of ultrasonic bolting technologies.

SBC Sensing Bolt Application System Architecture





ZIPPTORK Bolt Load Control



iting lech

For sensing and controlling bolt load generated in the bolted joint instantly throughout the bolting process



- 1. Patented design for direct sensing the bolt load induced on the joint during the bolting process.
- 2. With data logging functions and upload to a peripheral device or cloud server.
- 3. To be attached to the driving anvil of any torque tool for direct bolt load control.
- 4. Patented vibration-proof design, also suitable for impact torque tools.
- 5. RF2.4G wireless transmission and data collection.